

VS-NetCom 811RM



- Can control 8 x RS232 devices located virtually anywhere (via Ethernet or Internet)
- Lan interface 10BaseT/100BaseTx Ethernet
- Driver automatically finds NetCom devices in the network
- Configuration over Driver Panels, serial Port, Telnet, WEB Browser, SNMP
- Automatic mode switching between Driver and Raw Mode
- Supports TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS

Overview

VS NetCom 811RM is an industrial-strength network-based serial device server for connecting eight RS232 device like CNC, PLC, weighing scale, scanner and other devices directly to the 10/100Mbps Ethernet network running TCP/IP. In addition to allowing serial devices to get networked, any host (PC Server or Workstation) without network access can also access remote serial device via adding NetCom devices to the existing serial port. NetCom 811RM can be configured over Driver Panels, WEB Browser, serial Port, Telnet, SNMP and serves as a transparent serial channel without platform and distance limitation.

Applications

Industrial / Factory / Laboratory automation
SCADA system
Automatic warehouse control system
Building automation system
Wafer fabrication system
Self-service banking system
Retail system
Other remote and distributed serial devices control

Specification

Hardware

Processor: ARM 7 TDMI 50MHz
I/O controller: 16C550C or compatible
Memory: 8MB SDRAM, 1 MB Flash
Connector type: RJ45 for LAN, DSUB 9 male for serial Port

Interface

LAN interface: Auto-detecting 10BaseT/100BaseTx
Protocols: TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS
Serial interface: RS232
No. of port: 8, Speed up to 460Kbps
Available Modes: RS232 full duplex
Signals: RS232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND

Performance

Speed:	up to 460Kbps
Parity:	None, even, odd, space, mark
Data bits:	5, 6, 7, 8
Stop bits:	1, 1.5, 2
IRQ:	None
I/O address:	None

Operating Modes:

Driver mode:	VScom Driver for Windows NT 4.0, 2000, XP and 2003 Driver Mode creates virtual Com port.
TCP Raw Server:	Raw data transfer over TCP/IP. Accepts multiple incoming connections.
TCP Raw Client:	Raw data transfer over TCP/IP. Connects to multiple hosts or devices waiting for incoming connections.
TCP Advanced Settings:	Special settings for user-defined modes
UDP Mode:	Raw data transfer by UDP. The NetCom is client and server at the same time. With the timeout functionality and a configurable trigger string it can make defined UDP packets of incoming data.
Null Modem Tunnel:	Connecting two NetCom used as virtual null modem cable.
IP Modem:	The serial port emulates a standard modem. Operates by AT-commands, and dials to IP-Addresses instead of phone numbers. Windows "INF"-Driver provided for installation.

Power and Environment

Power requirements:	100 - 240V AC 47-63 Hz, 25VA
Dimension:	258×149×45 mm ³ (W×L×H) 278×155×46 mm ³ with DB9 connectors and DIN-RAIL ears 19" 1HU Rackmount
Operating Temp:	0°C - 60°C
Storage Temp:	-20°C - 85°C
Case:	SECC sheet metal (1mm)
Weight:	1.35kg

Special Features:

Installation:	Configuration utility automatically finds NetCom devices in the network
Operating mode:	Automatic mode switching between Driver and TCP RAW mode. With TCP Advanced settings it is possible to configure the NetCom for using it in multiple modes, so it decides automatically which mode should be used.

Configuration: Configuration over Driver Panels, NetCom Manager, WEB Browser, serial console, Telnet, SNMP

SNMP: special VScom MIB included

ART: no

DNS: Domain Name Server support

Serial interface: Serial Interface configurable with external switch

Firewall: Special precautions for Firewall environments

Firmware: Firmware update over WEB Browser, Telnet, ComPort

LEDs: LEDs for Power, Tx, Rx, LAN Link, LAN Speed

Security:

Password access: Every capabilities of configuration use the same password including SNMP V3

Ordering Information

Art.No: 672

Product Name: VS NetCom 811RM

Packing list: VS NetCom 811RM
CD-ROM with Driver and configuration software
Printed Quick Installation Guide